

PRODUCT DESCRIPTION

A ready set of elements for suspension and one-sided powering of a light-weight lighting fixture. When mounted, the fixture will emit light parallel to the surface. The fastener is equipped with a connection for one pole of current along with a 50 cm rod which acts as a conductor. The top fastener attaches the fixture, e.g. to a wooden or metal panel, and serves as a connection to the power supply

Fill empty fields

Product nr.

Fixture type


Company

Job name


Date




RELATED PROFILES



GIZA-LL profile
Ref: C0758




OPK-4 Profile
Ref: C0370




3035 Profile
Ref: 18039




JAZ Profile
Ref: B8547




SILER Profile
Ref: B9325




MICRO-ALU Profile
Ref: B1888




TAMI Profile
Ref: B5390




PDS-4-ALU Profile
Ref: B1718




PDS-ZM Profile
Ref: B7696




REGULOR Profile
Ref: B468+43




TEST-36 Profile
Ref: B6639




TEST-74 Profile
Ref: W4507




TETRA-43 Profile
Ref: W4476




TETRA-78 Profile
Ref: W4508




GIZA Profile
Ref: B5556




LIPOD Profile
Ref: B5554




DES Profile
Ref: 18030




GLADES Profile
Ref: 18036




3035-O Profile
Ref: B8441




PDS-ZMG Profile
Ref: C1418




MICRO-HG Profile
Ref: C1419




TAPO Profile
Ref: C1919



PDS-ZM-PLUS
Profile
Ref: C2056



4050 Profile
Ref: 18050



4050-W Profile
Ref: 18051