Profile LOKOM

Ref. A05553



IP20 IP65

- Hardly visible aluminum elements
- Easy maintenance
- Possibility to mount the power supply in the luminous part of the luminaire
- Small bending radius
- Possibility to use current modules with efficiency up to 190lm/W and CRI>90. Available upon request.

APPLICATION

- main and decorative lighting

MOUNTING

- recessed, using a dedicated mounting track

ADDITIONAL INFORMATION

- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	**aluminum**
Possible fixture IP	**20, 65**
Possible fixture shapes	**linear, polygonal**
Profile cross-section	**rectangular**
Width	**30.2 mm**
Height	**24.5 mm**
LED gluing width A	**24 mm**
Number of LED strips A (8 mm wide)	**2**
Width of the glow	**22 mm**
Max power of a single KLUŚ LED strip	**24 W/m**
Possibility of obtaining a line of light	**yes**
Possibility of bending	**yes**
Radius of the light arc	**yes**
Inward	**3000 mm**
Outdoor	**3000 mm**
Building type	**Commercial, Entertainment/ Arts, HoReCa object**

Color	Length	Ref
silver anodized	1000 mm	**A05553A_1**
	2005 mm	**A05553A_2**
	3010 mm	**A05553A_3**
black anodized	1000 mm	**A05553A07_1**
	2005 mm	**A05553A07_2**
	3010 mm	**A05553A07_3**
white lacquered	3010 mm	**A05553L10OD_3**
	2005 mm	**A05553L10OD_2**
	1000 mm	**A05553L10OD_1**
black lacquered	3010 mm	**A05553L07OD_3**

Standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)

Profile LOKOM

Ref. A05553

Facility zone	**office, lobby / foyer, media rooms / av**
The cover is cut to the length of the profile	**yes**
Can be easily connected into runs	**yes**
Mounting to drywall	**yes**
Wire out back of extrusion	**yes**

LINE OF LIGHT TABLE

LED tape	LIGER-22 satin	LIGER-22 black	HS-22 frosted	G-22R satin	G-22S satin
K-1275-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-0480-24	✓ (1)	X	X	X	**X**
K-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-0360-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-0720-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-1080-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-0500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-1500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CB-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HD-1260-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-0360-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-0720-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-1080-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-0500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-1500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-CB-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-GHD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-GHD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-HD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-HD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-HD-1260-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-2300-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**

Profile LOKOM

Ref. A05553

K-2400-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CR-1210-24	✓ (1)	X	X	X	**X**
K-CR-1220-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CR-1275-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CRHD-1820-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CRHD-1910-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CR-0480-24	✓ (1)	X	X	X	**X**
K-CR-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-CR-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HEHD-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HEHD-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HEHD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-HEHD-1920-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-VHE-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-VHE-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-VHE-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-RGB27T65-1200-24	✓ (1)	X	X	X	**X**
K-RGBW-1530-24	✓ (1)	X	X	X	**X**
KWP-GRGB-1530-24	✓ (1)	X	X	X	**X**
K-RGB-1200-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-RGB-1200-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-18D30-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-18D30-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-27T50-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
K-VBT-0720-24	✓ (1)	X	X	X	**X**
K-SD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ **(1)**
KWP-RGBW-1530-24	✓ (1)	X	X	X	**X**

Description

✓ - Line of Light for a number (X) of rows - Pixel free imaging

X - Visible Dotting from Diodes

HL - Centered Line of Light - Concentrated in middle

HL (X) - Centered Line of Light for a number (X) of rows - Concentrated in middle

Line of Light Guide



Clean Line of Light (Pixel free imaging)



Centered Line of Light



Visible Dotting from Diodes

Profile LOKOM
Ref. A05553

KLUŚ Inspiring Solutions

SAMPLE PROJECTS





SIMILAR PROFILES



Profile KOZEL
A06454



Profile LARKO
A05552



Profile LIPOD
A05554

RELATED ACCESSORIES > COVERS

NAME			KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
Optics DOT-22	NEW		- constant voltage version			black	B20L07-ML30-0900-24
							B20L07-ML40-0900-24
							B34L07-ML30-0900-24
							B34L07-ML40-0900-24
							B48L07-ML30-0900-24
							B48L07-ML40-0900-24
							B20L10-ML30-0900-24
							B20L10-ML40-0900-24
							B34L10-ML30-0900-24
						white	B34L10-ML40-0900-24
							B48L10-ML30-0900-24

Profile LOKOM

Ref. A05553

NAME		KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
						B48L10-ML40-0900-24
Cover G-22R		- indoor use - Perfectly diffusing	PMMA	20 %	black	B17006B
				71 %	satin	B17006S
				89 %	semi-transparent	B17006T
				94 %	clear	B17006C
Cover G-22S		- indoor use - Perfectly diffusing	PMMA	15 %	black	B17013B
				86 %	satin	B17013S
				89 %	semi-transparent	B17013T
Cover HS-22		- For indoor and outdoor applications - UV resistant	PC	65 %	frosted	B17011F
				88 %	clear	B17011C
				90.5 %	microprism	B17011M
Cover LIGER-22		- hight light quality - For indoor and outdoor applications - Ease of obtaining a line of light - Perfectly diffusing	PC	22 %	black	B17032B
				70 %	satin	B17032S
Cover BENCO-22		- For indoor and outdoor applications - UV resistant	Silikon	62 %	frosted	B17209F

RELATED ACCESSORIES > END CAPS

NAME		MATERIAL	COLOR	REF.
End cap LOKOM		PP	black	C24005C07
			gray	C24005C02
			silver	C24005L01
		PET-G	black	C28285C07
			gray	C28285C02
			white	C28285L10

RELATED ACCESSORIES > PROFILE TECHNICZNE

Profile LOKOM

Ref. A05553

Name	Material	Color	Ref.
Profile TEKUS	aluminum	silver non anodized	A06638V
Profile TEKUS-ZM	aluminum	silver non anodized	A01293
Profile TEKNIK-ZM-TK	aluminum	silver non anodized	A01554

RELATED ACCESSORIES > RELATED LED > WHITE MONO

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-0360-24 3.6 W/m, IP20 NEW		20	3.6 W/m	K-27-0360-24 K-30-0360-24 K-35-0360-24 K-40-0360-24 K-50-0360-24
LED tape K-HD-0430-24 4.3 W/m, IP20 NEW		20	4.3 W/m	K-HD27-0430-24 K-HD30-0430-24 K-HD35-0430-24 K-HD40-0430-24 K-HD50-0430-24
LED tape K-0480-24	- universal for basic applications	20	4.8 W/m	K-27-0480-24 K-30-0480-24 K-35-0480-24 K-40-0480-24 K-50-0480-24
LED tape K-HD-0480-24	- high LED density - Ease of obtaining a line of light	20	4.8 W/m	K-HD27-0480-24 K-HD30-0480-24 K-HD35-0480-24 K-HD40-0480-24 K-HD50-0480-24
LED tape K-0500-24 5 W/m, IP20 NEW		20	5 W/m	K-30-0500-24 K-40-0500-24
LED tape K-0720-24 7.2 W/m, IP20 NEW		20	7.2 W/m	K-27-0720-24 K-30-0720-24 K-35-0720-24 K-40-0720-24 K-50-0720-24
LED tape K-HD-0830-24 8.3 W/m, IP20 NEW		20	8.3 W/m	K-HD27-0830-24 K-HD30-0830-24 K-HD35-0830-24 K-HD40-0830-24 K-HD50-0830-24
LED tape K-0960-24	- universal for basic applications	20	9.6 W/m	K-27-0960-24 K-30-0960-24 K-30-0960-24-R30 K-35-0960-24 K-40-0960-24 K-40-0960-24-R30 K-50-0960-24 K-65-0960-24
LED tape K-HD-0960-24	- high LED density - Ease of obtaining a line of light	20	9.6 W/m	K-HD27-0960-24 K-HD30-0960-24 K-HD35-0960-24 K-HD40-0960-24 K-HD50-0960-24
LED tape K-1000-24 10 W/m, IP20 NEW		20	10 W/m	K-30-1000-24 K-40-1000-24
LED tape K-CB-1000-24 10 W/m, IP20 NEW		20	10 W/m	K-CB27-1000-24 K-CB30-1000-24 K-CB40-1000-24 K-CB50-1000-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-1080-24 10.8 W/m, IP20 NEW		20	10.8 W/m	K-27-1080-24 K-30-1080-24 K-35-1080-24 K-40-1080-24 K-50-1080-24
LED tape K-HD-1260-24 12.6 W/m, IP20 NEW		20	12.6 W/m	K-HD27-1260-24 K-HD30-1260-24 K-HD35-1260-24 K-HD40-1260-24 K-HD50-1260-24
LED tape K-1275-24	- universal for basic applications	20	14.4 W/m	K-22-1275-24 K-25-1275-24 K-27-1275-24 K-30-1275-24 K-35-1275-24 K-40-1275-24 K-50-1275-24
LED tape K-1440-24	- universal for basic applications	20	14.4 W/m	K-27-1440-24 K-30-1440-24 K-30-1440-24-R30 K-35-1440-24 K-40-1440-24 K-40-1440-24-R30 K-50-1440-24
LED tape K-HD-1440-24	- high LED density - Ease of obtaining a line of light	20	14.4 W/m	K-HD27-1440-24 K-HD30-1440-24 K-HD35-1440-24 K-HD40-1440-24 K-HD50-1440-24
LED tape K2-1440-24 14.4 W/m, IP20 NEW		20	14.4 W/m	K2-27-1440-24 K2-30-1440-24 K2-35-1440-24 K2-40-1440-24 K2-50-1440-24
LED tape K-1500-24 15 W/m, IP20 NEW		20	15 W/m	K-30-1500-24 K-40-1500-24
LED tape K2-1920-24	- LED double-row strip - quick installation	20	19.2 W/m	K2-27-1920-24 K2-30-1920-24 K2-35-1920-24 K2-40-1920-24 K2-50-1920-24
LED tape K3-2160-24 21.6 W/m, IP20 NEW	- Three-row LED strip - quick installation	20	21.6 W/m	K3-27-2160-24 K3-30-2160-24 K3-35-2160-24 K3-40-2160-24 K3-50-2160-24
LED tape K-2300-24	- high power	20	23 W/m	K-30-2300-24 K-40-2300-24
LED tape K-2400-24	- high power	20	24 W/m	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24
LED tape K3-2880-24	- Three-row LED strip - quick installation	20	28.8 W/m	K3-27-2880-24 K3-30-2880-24 K3-35-2880-24 K3-40-2880-24 K3-50-2880-24
LED tape KWP-0360-24 3.6 W/m, IP65 NEW		65	3.6 W/m	KWP-27-0360-24 KWP-30-0360-24 KWP-35-0360-24 KWP-40-0360-24 KWP-50-0360-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape KWP-GHD-0430-24 4.3 W/m, IP65 NEW		65	4.3 W/m	KWP-GHD27-0430-24 KWP-GHD30-0430-24 KWP-GHD35-0430-24 KWP-GHD40-0430-24 KWP-GHD50-0430-24
LED tape KWP-HD-0430-24 4.3 W/m, IP65 NEW		65	4.3 W/m	KWP-HD27-0430-24 KWP-HD30-0430-24 KWP-HD35-0430-24 KWP-HD40-0430-24 KWP-HD50-0430-24
LED tape KWP-0480-24	- universal for basic applications	65	4.8 W/m	KWP-27-0480-24 KWP-30-0480-24 KWP-35-0480-24 KWP-40-0480-24 KWP-50-0480-24
LED tape KWP-GHD-0480-24	- high LED density - Ease of obtaining a line of light	65	4.8 W/m	KWP-GHD27-0480-24 KWP-GHD30-0480-24 KWP-GHD35-0480-24 KWP-GHD40-0480-24 KWP-GHD50-0480-24
LED tape KWP-0500-24 5 W/m, IP65 NEW		65	5 W/m	KWP-30-0500-24 KWP-40-0500-24
LED tape KWP-0720-24 7.2 W/m, IP65 NEW		65	7.2 W/m	KWP-27-0720-24 KWP-30-0720-24 KWP-35-0720-24 KWP-40-0720-24 KWP-50-0720-24
LED tape KWP-GHD-0830-24 8.3 W/m, IP65 NEW		65	8.3 W/m	KWP-GHD27-0830-24 KWP-GHD30-0830-24 KWP-GHD35-0830-24 KWP-GHD40-0830-24 KWP-GHD50-0830-24
LED tape KWP-HD-0830-24 8.3 W/m, IP65 NEW		65	8.3 W/m	KWP-HD27-0830-24 KWP-HD30-0830-24 KWP-HD35-0830-24 KWP-HD40-0830-24 KWP-HD50-0830-24
LED tape KWP-0960-24	- universal for basic applications	65	9.6 W/m	KWP-27-0960-24 KWP-30-0960-24 KWP-35-0960-24 KWP-40-0960-24 KWP-50-0960-24 KWP-65-0960-24
LED tape KWP-GHD-0960-24	- high LED density - Ease of obtaining a line of light	65	9.6 W/m	KWP-GHD27-0960-24 KWP-GHD30-0960-24 KWP-GHD35-0960-24 KWP-GHD40-0960-24 KWP-GHD50-0960-24
LED tape KWP-1000-24 10 W/m, IP65 NEW		65	10 W/m	KWP-30-1000-24 KWP-40-1000-24
LED tape KWP-CB-1000-24 10 W/m, IP65 NEW		65	10 W/m	KWP-CB27-1000-24 KWP-CB30-1000-24 KWP-CB40-1000-24 KWP-CB50-1000-24
LED tape KWP-1080-24 10.8 W/m, IP65 NEW		65	10.8 W/m	KWP-27-1080-24 KWP-30-1080-24 KWP-35-1080-24 KWP-40-1080-24 KWP-50-1080-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape KWP-GHD-1260-24 12.6 W/m, IP65		65	12.6 W/m	KWP-GHD27-1260-24 KWP-GHD30-1260-24 KWP-GHD35-1260-24 KWP-GHD40-1260-24 KWP-GHD50-1260-24
LED tape KWP-HD-1260-24 12.6 W/m, IP65 NEW		65	12.6 W/m	KWP-HD27-1260-24 KWP-HD30-1260-24 KWP-HD35-1260-24 KWP-HD40-1260-24 KWP-HD50-1260-24
LED tape KWP-1440-24	- universal for basic applications	65	14.4 W/m	KWP-27-1440-24 KWP-30-1440-24 KWP-35-1440-24 KWP-40-1440-24 KWP-50-1440-24
LED tape KWP-GHD-1440-24	- high LED density - Ease of obtaining a line of light	65	14.4 W/m	KWP-GHD27-1440-24 KWP-GHD30-1440-24 KWP-GHD35-1440-24 KWP-GHD40-1440-24 KWP-GHD50-1440-24
LED tape KWP-1500-24 15 W/m, IP65 NEW		65	15 W/m	KWP-30-1500-24 KWP-40-1500-24

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-HEHD-0480-24	- CRI over 95 - High Efficacy	20	4.8 W/m	K-HEHD22-0480-24 K-HEHD25-0480-24 K-HEHD27-0480-24 K-HEHD30-0480-24 K-HEHD35-0480-24 K-HEHD40-0480-24 K-HEHD50-0480-24
LED tape K-VHE-0480-24	- universal for basic applications - high efficacy - High Efficacy	20	4.8 W/m	K-VHE27-0480-24 K-VHE30-0480-24 K-VHE35-0480-24 K-VHE40-0480-24 K-VHE50-0480-24
LED tape K-HEHD-0960-24	- CRI over 95 - High Efficacy	20	9.6 W/m	K-HEHD22-0960-24 K-HEHD25-0960-24 K-HEHD27-0960-24 K-HEHD30-0960-24 K-HEHD35-0960-24 K-HEHD40-0960-24 K-HEHD50-0960-24
LED tape K-VHE-0960-24	- universal for basic applications - high efficacy - High Efficacy	20	9.6 W/m	K-VHE27-0960-24 K-VHE30-0960-24 K-VHE35-0960-24 K-VHE40-0960-24 K-VHE50-0960-24
LED tape K-HEHD-1440-24	- CRI over 95 - High Efficacy	20	14.4 W/m	K-HEHD22-1440-24 K-HEHD25-1440-24 K-HEHD27-1440-24 K-HEHD30-1440-24 K-HEHD35-1440-24 K-HEHD40-1440-24 K-HEHD50-1440-24
LED tape K-VHE-1440-24	- universal for basic applications - high efficacy - High Efficacy	20	14.4 W/m	K-VHE27-1440-24 K-VHE30-1440-24 K-VHE35-1440-24 K-VHE40-1440-24 K-VHE50-1440-24

Profile LOKOM
Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-HEHD-1920-24	- CRI over 95 - High Efficacy	20	19.2 W/m	K-HEHD22-1920-24 K-HEHD25-1920-24 K-HEHD27-1920-24 K-HEHD30-1920-24 K-HEHD35-1920-24 K-HEHD40-1920-24 K-HEHD50-1920-24

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CCT

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-RGB-0700-24V	- RGB	20	7 W/m	K-RGB-0700-24V
LED tape K-RGB-1200-24	- RGB	20	12 W/m	K-RGB-1200-24
LED tape K-RGB27T65-1200-24	- RGB+Tunable White	20	12 W/m	K-RGB27T65-1200-24
LED tape KWP-RGB-0700-24	- RGB	65	7 W/m	KWP-RGB-0700-24
LED tape KWP-RGB-1200-24	- RGB	65	12 W/m	KWP-RGB-1200-24
LED tape KWP-GRGB-1530-24 15.3 W/m, IP65 NEW	- RGBW - high LED density	65	15.3 W/m	KWP-GRGB30-1530-24 KWP-GRGB40-1530-24

RELATED ACCESSORIES > RELATED LED > CRI 95+

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-CR-0480-24	- universal for basic applications - CRI over 95	20	4.8 W/m	K-CR27-0480-24 K-CR30-0480-24 K-CR35-0480-24 K-CR40-0480-24 K-CR50-0480-24
LED tape K-CR-1210-24	- CRI over 95	20	4.8 W/m	K-CR22-1210-24 K-CR25-1210-24 K-CR27-1210-24 K-CR30-1210-24 K-CR35-1210-24 K-CR40-1210-24 K-CR50-1210-24
LED tape K-CRHD-1910-24	- CRI over 95 - high LED density	20	9.1 W/m	K-CRHD22-1910-24 K-CRHD25-1910-24 K-CRHD27-1910-24 K-CRHD30-1910-24 K-CRHD35-1910-24 K-CRHD40-1910-24 K-CRHD50-1910-24
LED tape K-CR-0960-24	- universal for basic applications - CRI over 95	20	9.6 W/m	K-CR27-0960-24 K-CR30-0960-24 K-CR35-0960-24 K-CR40-0960-24 K-CR50-0960-24
LED tape K-CR-1220-24	- CRI over 95	20	9.6 W/m	K-CR22-1220-24 K-CR25-1220-24 K-CR27-1220-24 K-CR30-1220-24 K-CR35-1220-24 K-CR40-1220-24 K-CR50-1220-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-CR-1275-24	- CRI over 95	20	14.4 W/m	K-CR22-1275-24 K-CR25-1275-24 K-CR27-1275-24 K-CR30-1275-24 K-CR35-1275-24 K-CR40-1275-24 K-CR50-1275-24
LED tape K-CR-1440-24	- universal for basic applications - CRI over 95	20	14.4 W/m	K-CR27-1440-24 K-CR30-1440-24 K-CR35-1440-24 K-CR40-1440-24 K-CR50-1440-24
LED tape K-CRHD-1820-24	- CRI over 95 - high LED density	20	18.25 W/m	K-CRHD22-1820-24 K-CRHD25-1820-24 K-CRHD27-1820-24 K-CRHD30-1820-24 K-CRHD35-1820-24 K-CRHD40-1820-24 K-CRHD50-1820-24
LED tape KWP-CR-0480-24	- universal for basic applications - CRI over 95	65	4.8 W/m	KWP-CR27-0480-24 KWP-CR30-0480-24 KWP-CR35-0480-24 KWP-CR40-0480-24 KWP-CR50-0480-24
LED tape KWP-CR-0960-24	- universal for basic applications - CRI over 95	65	9.6 W/m	KWP-CR27-0960-24 KWP-CR30-0960-24 KWP-CR35-0960-24 KWP-CR40-0960-24 KWP-CR50-0960-24

RELATED ACCESSORIES > RELATED LED > BENDABLE

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-VBT-0720-24	- LED tape for bent profiles	20	7.2 W/m	K-VBT27-0720-24 K-VBT30-0720-24 K-VBT35-0720-24 K-VBT40-0720-24 K-VBT50-0720-24
LED tape K-BTRGB40-1510-24		20	15.1 W/m	K-BTRGB40-1510-24

RELATED ACCESSORIES > RELATED LED

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-SD-1440-24		20	14.4 W/m	K-SD27-1440-24 K-SD30-1440-24 K-SD35-1440-24 K-SD40-1440-24
LED tape KWP-RGB27T50-1200-24, 2700K, 390 lm/m, 12 W/m, IP65		65	12 W/m	KWP-RGB27T50-1200-24
LED tape KWP-RGBW-1530-24 15.3 W/m, IP65 NEW	- RGBW - high LED density	65	15.3 W/m	KWP-RGB30-1530-24 KWP-RGB40-1530-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-18D30-0960-24	- Dim To Warm LED Tape	20	9.6 W/m	K-18D30-0960-24

Profile LOKOM
Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-27T50-1440-24	- RGB+Tunable White	20	14.4 W/m	K-27T50-1440-24
LED tape KWP-18D30-0960-24		65	9.6 W/m	KWP-18D30-0960-24

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > LATCHES

Name	Material	Color	Ref.
Latch TEKNIK	PP	white	C24003C10

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONNECTORS

Name	Material	Color	Ref.
Connector ZM	stainless steel	silver silver silver silver black colored colorless non colored black colored silver black colored silver black colored silver black colored silver black colored silver black colored silver silver	42716 42717 42720 42728 C24797C07 C24797N00 C28070C07 C28070N00 C28071C07 C28071N00 C28072C07 C28072N00 C28073C07 C28073N00 C28074C07 C28074N00 C28075C07 C28075N00 C28243N00
Connector ZM-NA	stainless steel	silver	42305 42339 42723 42724 42725 C28242N00
Connector ZM-T	stainless steel	black colored silver black colored silver black colored silver	C28076C07 C28076N00 C28077C07 C28077N00 C28078C07 C28078N00
Connector ZM-PION	stainless steel	silver silver silver silver silver black colored silver black colored silver black colored silver black colored silver black colored silver black colored silver	42314 42316 42320 42718 42719 C28084C07 C28084N00 C28085C07 C28085N00 C28086C07 C28086N00 C28087C07 C28087N00 C28088C07 C28088N00

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SPRINGS FOR RECESSED MOUNT AND MOUNTING TRACKS

Profile LOKOM

Ref. A05553

Name	Material	Color	Ref.
Spring KMA	stainless steel	silver	C24503N00

RELATED ACCESSORIES > ELECTRONICS > SWITCHES

Name	Key features	IP protection rating	Ref.
Proximity switch UNI-11 NEW	- touchless switch - width 11mm	20	E61603
Proximity switch UNI-11P NEW	- touchless switch - width 11mm - factory pre-soldered wires	20	E61604
Proximity switch UNI-P	- touchless switch - width only 7mm - factory pre-soldered wires	20	E61580
Proximity switch UNI	- touchless switch - width only 7mm	20	E61579