

PRODUCT DESCRIPTION

Standard conductive fastener for light-weight fixtures. Power is supplied outside the fastener to a power connector. One current pole is powered from one fastener that is equipped with a LONGITUDINAL Hole for the FI-3 ROD, which acts as a power conductor

Fill empty fields

Product nr.

Fixture type

Company


Job name

Date



TECHNICAL SPECIFICATION

TECHNICAL DRAWING






RELATED PROFILES



GIZA-LL profile Ref: C0758



3035 Profile Ref: 18039



JAZ Profile Ref: B8547



SILER Profile Ref: B9325



MICRO-ALU Profile Ref: B1888



TAMI Profile Ref: B5390



PDS-4-ALU Profile Ref: B1718



PDS-ZM Profile Ref: B7696



REGULOR Profile Ref: B468+43



TEST-74 Profile Ref: W4507



TETRA-43 Profile Ref: W4476



TETRA-78 Profile Ref: W4508



GIZA Profile Ref: B5556



LIPOD Profile Ref: B5554



3035-O Profile Ref: B8441



PDS-4-PLUS Profile Ref: C1263



PDS-ZMG Profile Ref: C1418



TAPO Profile Ref: C1919



PDS-ZM-PLUS Profile Ref: C2056



4050 Profile Ref: 18050



4050-W Profile Ref: 18051



RELATED PRODUCTS

ACCESSORIES




100 PUSZ brass chrome Rod 1 m Ref: 42518



Rod 1m Ref: 42501



Brass chrome FI-3 Steel FI-3 Rod 53 cm Ref: 1528



Steel wire FI-1 1m Ref: 1397