

# The cover has a matt black surface that turns white when the light is turned on, line of light at 120LED/m (9.6W/m) in profiles with minimal deep 19 mm. The cover is made of UV-resistant PMMA. When the LEDs are off,

- They blend in with dark lighting fixtures and dark surfaces of ceilings or walls
- A surprising light effect when the light is switched on

# Fill empty fields

it is black. The best visual effect is obtained in profiles that are black inside.

Product nr.

Fixture type

Company

Job name

Date



## **TECHNICAL SPECIFICATION**

## **Application**


Decorative lighting.

#### **Assembly**

Snap-in in dedicated profiles.

Material	PMMA
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	yes

# **TECHNICAL DRAWING**





# **RELATED PROFILES**



GIZA-LL profile Ref: C0758



KOZUS-CR Profile Ref: C0600



GIZA Profile Ref: B5556



LIPOD Profile Ref: B5554



LOKOM Profile Ref: B5553



LARKO Profile Ref: B5552



LESTO Profile Ref: B5551



OPAC-30 Profile Ref: B6164



LOC-30 Profile Ref: 18015



KOZEL Profile Ref: B6454



KOZUS Profile Ref: B7823



KIDES-DUO Profile Ref: 18032



STEPUS Profile Ref: 18038



WERKIN Profile Ref: 18025




GIZA-DUO-LL Profile Ref: C2162



# **RELATED PRODUCTS**

## MARKETING MATERIALS





Display P230-90154M Ref: 90154M

Foam 70271 Ref: 70271